

PRODUCT STACKER/DESTACKER QUOTATION WORKSHEET

Company _____ Date _____
Contact _____ Quote Due _____ Desired Delivery _____
Phone No. _____ Contact Email _____ State _____
Omni Sales Contact _____ Quote #: _____
Quantity _____

Operation:

- Stack
- Destack
- Both

Environment:

- Dry
- Wet
- Washdown
- Cold/Hot
- Dirty
- Other: _____

Configuration:

- Straight Thru
- 90 Degree Left Hand
- 90 Degree Right Hand

Pneumatics: (Parker)

- Cylinders Mounted Only
- Cylinders Mounted & Plumbed to Valves
- Cylinders Mounted & Plumbed to Valve Board with Filter/Regulator & Safety Lockout

Lifting Mechanism:

- Pneumatic Cylinder
- Hydraulic Scissor Lift
- Mechanical Ball Screw

Plant Voltage:

- 110V Single Phase
- 460V Three Phase
- 220V Single Phase
- 208V Three Phase
- 220V Three Phase
- 575V Three Phase

Fork Mechanism:

- Pneumatic Cylinder
- Hydraulic Cylinder
- Other: _____

Control Voltage:

- 120V/1PH/60HZ
- 24V DC
- Other: _____

Product Size: (In Direction of Travel)

Length: _____ Width: _____
Height: _____ Weight: _____
of Products: _____ Stack Height: _____
Products per Minute: _____
Products per Hour: _____
Product: _____
(Pallet, Rack, Tire, Tote, Other)
Material: _____
(Wood, Plastic, Steel, Other)

Electrical: (Allen-Bradley)

- None
- Sensors for Product & Machine Position Mounted and Wired to J-Box
- Control Panel with PLC Logic & Sensors Mounted and Wired

Infeed:

Conveyed In Fork Truck Load
Elevation: _____ Speed: _____

Integral Conveyor:

- Chain Driven Live Roller
- Chain Conveyor
- By Others

Discharge:

Conveyed Out Fork Truck Unload
Elevation: _____ Speed: _____

Other: _____

Finish:

- Standard Enamel Paint
- Epoxy Paint
- Stainless Steel
- Other: _____

Approval Drawing Required: Yes No