Omni Metalcraft_{corp}.

Submit to: info@omni.com www.omni.com

BELT DRIVEN LIVE ROLLER CONVEYOR QUOTATION WORKSHEET

Company	[Date	
Contact		Desired Delivery	
Phone No.:		-	
Omni Sales Contact:	Qu	uote #:	
Quantity:			
Product Specs:	Horsepower:	·	
	Drive Type: 🗆	🕽 Under Hung 📮 Shaft Mount	
Width (inches): Length (inches):		Side Mount (Chain Driven)	
Height (inches):Weight (lbs):		on: 🖵 Infeed End 🖵 Center	
Min:			
Width (inches): Length (inches): Height (inches): Weight (lbs):			
Description:		5	
Max. Qty.: Total Live Load:		-	
Temperature			
Environment:		Conveyor Description: See Layout: 🖵 Attached	
Product:			
		Location:	
Conveyor Construction:	Components		
Light Duty BDLR (Bolt-Together)	Qty.	Description	
Galvanized Finish Coat		'"LHP	
Medium Duty BDLR (Welded/Finish Coat)		'" LHP	
Heavy Duty BDLR (Welded/Finish Coat)		'" LHP	
Conveyor Finish:		° V-Belt Driven Curve	
Painted Epoxy Painted		Slaved Driven LH RH	
Powder Coated Color/RAL:		○ V-Belt Driven Curve Spur	
Stainless Steel		• V-Belt Driven Straight Spur	
Roller Specs.:		□ Slaved □ Driven □ LH □ RH	
1.9 in. dia. x 16 ga. galv. Roller c/c:	Zara Brazoura		
1.9 in. dia. x .145 in. wall Precision	Bearings	'- "L. HP	
□ 2 1/2 in. dia. x 11 ga. □ Other:		Zone Length	
Application Type:		Trigger Roller I Photo-Eye	
Transportation Type	0		
Minimum Pressure Type	Conveyor Ac		
Zero Pressure Type	-	Air Operated	
Between Frame Width:		Other:	
(Standard B.F.'s: 14, 18, 22, 26, 32, 38)			
Support Type:	Other:		
Legs Ceiling Supports Nor			
TOR:			
Speed:			
FPM: Fixed Variable (1			