

## MODULAR TABLE TOP CONVEYOR QUOTATION WORKSHEET

Company \_\_\_\_\_ Date \_\_\_\_\_  
 Contact \_\_\_\_\_ Quote Due \_\_\_\_\_ Desired Delivery \_\_\_\_\_  
 Phone No.: \_\_\_\_\_ Contact Email: \_\_\_\_\_ State \_\_\_\_\_  
 Omni Sales Contact: \_\_\_\_\_ Quote #: \_\_\_\_\_  
 Quantity: \_\_\_\_\_

### Product Specs:

Max:  
 - Width (inches): \_\_\_\_\_ Length (inches): \_\_\_\_\_  
 - Height (inches): \_\_\_\_\_ Weight (lbs): \_\_\_\_\_  
 Min:  
 - Width (inches): \_\_\_\_\_ Length (inches): \_\_\_\_\_  
 - Height (inches): \_\_\_\_\_ Weight (lbs): \_\_\_\_\_  
 Description: \_\_\_\_\_  
 Max. Qty.: \_\_\_\_\_ Total Live Load\*: \_\_\_\_\_  
 Temperature  
 -Environment: \_\_\_\_\_  
 -Product: \_\_\_\_\_  
 Wet  Dry  Other \_\_\_\_\_

### Bolt Together Conveyor Construction:

- Mild Steel Powder Coat
  - RAL Color: \_\_\_\_\_
- Stainless Steel
  - Mill Finish
  - Polished

### Welded Construction Available for Custom Applications

### Frame Type:

- Open Top
- Closed Top

### Conveyor Components:

Qty.	Component	Length/Degree
_____	Drive End	_____
_____	Intermediate	_____
_____	Intermediate	_____
_____	Intermediate	_____
_____	Idle End	_____
_____	Curve	_____
_____	Curve	_____
_____	90° Dead Plate Turn	N/A
_____	Parallel Transfer	N/A
_____	Cope	N/A

### Table Top Chain Specs:

Chain Width: \_\_\_\_\_ Inches Chain Style: \_\_\_\_\_

### Application Information:

- Product Enters By:
- Conveyed On  Fork Truck
  - Robot  Other \_\_\_\_\_
- Product Exits By:
- Conveyed off  Fork Truck
  - Robot  Other \_\_\_\_\_

- Quantity of Starts and Stops per Day \_\_\_\_\_
- \*Will the Conveyor be started with a load??  
 Yes  No  Soft Start Required?

### Support Type:

- Legs  Ceiling Supports
- None Top of Belt: \_\_\_\_\_

### \*Speed:

- Fixed (FPM) \_\_\_\_\_
- Variable Low Speed (FPM) \_\_\_\_\_
- High Speed (FPM) \_\_\_\_\_
- AC Speed Controller  DC Speed Controller

### Drive Type:

- Under Hung  Shaft Mount

### Plant Voltage:

- 110V Single Phase  460V Three Phase
- 220V Single Phase  208V Three Phase
- 220V Three Phase  575V Three Phase

Other: \_\_\_\_\_

**\*Unless otherwise noted Omni will assume that conveyors are fully loaded and require soft starts.**

Approval Drawing Required:  Yes  No